

File 347:JAPIO OCE 1976-1998/Mar. (UPDATED 980630)  
(c) 1998 JPO & JAPIO

1/9/1

DIALOG(R) File 347:JAPIO

(c) 1998 JPO & JAPIO. All rts. reserv.

04110643

MOUNTING STRUCTURE OF SEMICONDUCTOR DEVICE AND MOUNTING METHOD OF  
SEMICONDUCTOR DEVICE

PUB. NO.: 05-102343 [JP 5102343 A]  
PUBLISHED: April 23, 1993 (19930423)  
INVENTOR(s): SATO HIDEKAZU  
APPLICANT(s): SEIKO EPSON CORP [000236] (A Japanese Company or Corporation)  
, JP (Japan)  
APPL. NO.: 03-260072 [JP 91260072]  
FILED: October 08, 1991 (19911008)  
INTL CLASS: [5] H01L-023/15; H05K-013/04  
JAPIO CLASS: 42.2 (ELECTRONICS -- Solid State Components); 42.1  
(ELECTRONICS -- Electronic Components)  
JAPIO KEYWORD: R002 (LASERS)  
JOURNAL: Section: E, Section No. 1417, Vol. 17, No. 453, Pg. 68,  
August 19, 1993 (19930819)

#### ABSTRACT

PURPOSE: To provide a method by which the reliability on the connection is high and which never causes electric conductivity trouble, in case of mounting a semiconductor element on a glass board, with the active face opposite to it.

CONSTITUTION: A semiconductor element 1 is loaded on a wiring board 4 where a through hole 9 is opened, and the adhesive for fixing is hardened by heat. Moreover, in case of having used a photosetting adhesive, it can be made the hardening from the rear of the semiconductor device and the hardening from the rear of the glass board. This way, by having opened a through hole, the adhesive can be escaped to outside, so it does not give stress to the connection. Moreover, even if trouble should be found, the semiconductor device could be removed simply from the glass wiring board.